



Zettachring 6, 70567 Stuttgart, Germany
 Tel: +49-711-13257-0 Fax: +49-711-13257-89
 E-Mail: info.tb@tosoh.com
 Web: www.tosohbioscience.com

3604 Horizon Drive, Suite 100, King of Prussia, PA 19406, USA
 Tel: +1-484-805-1219 Fax: +1-610-272-3028
 E-Mail: info.tbl@tosoh.com
 Web: www.tosohbioscience.com

PRODUCT SPECIFICATION SHEET

Product Name: Toyopearl® PPG-600M (hydrophobic interaction resin – weakly hydrophobic)

HW - 60 — (O-CH₂CH₂CH₂)_n-OH

Part Numbers:

21301	Toyopearl PPG-600M, 65 µm, 25 mL
21302	Toyopearl PPG-600M, 65 µm, 100 mL
21303	Toyopearl PPG-600M, 65 µm, 1 L
21304	Toyopearl PPG-600M, 65 µm, 5 L
21380	ToyoScreen PPG-650M, 1 mL x 6 ea.
21381	ToyoScreen PPG-650M, 5 mL x 6 ea.
21398	ToyoScreen HIC Mix Pack, 1 mL x 6 grades x 1 ea. (Ether, Butyl-650, Hexyl, Phenyl, PPG, SuperButyl)
21399	ToyoScreen HIC Mix Pack, 5 mL x 6 grades x 1 ea. (Ether, Butyl-650, Hexyl, Phenyl, PPG, SuperButyl)
21400	ToyoScreen Column Holder
42194	ToyoScreen Column Holder with fittings

Product Description: Toyopearl is a methacrylic polymer incorporating high mechanical and chemical stability. Resins are available as non-functionalised “HW” series resins for size exclusion separations, and derivatised with surface chemistries for alternative modes of chromatography such as ion exchange, hydrophobic interaction or affinity separations.

Toyopearl PPG-600M chromatographic resin is designed for hydrophobic interaction chromatography. This chromatographic mode separates molecules on the basis of hydrophobic interactions between the sample and the resin. The separation is usually accomplished in buffered aqueous solution with a gradient of decreasing ionic strength. Toyopearl PPG-600M incorporates a higher binding capacity for antibodies and a high recovery.

Formulation: Particulate resin (spherical), available in particle sizes (mean diameter):
 65 µm = “M” grade
 Supplied as slurry in 20 % ethanol (v/v).

Physicochemical Specifications:

▪ Appearance	White resin slurry which settles upon standing
▪ Particle Size Distribution (>80 % within range)	40 – 90 µm for PPG-600M
▪ Exclusion Limit	5 x 10 ⁷ Dalton (Pullulan)
▪ Mean Pore Diameter	500 Å
▪ Pressure drop across the column	max. 7 bar (recommended)
▪ Operating Linear Flowrate	normally 10 – 600 cm/hour (depending on particle size)
▪ Protein Adsorption Capacity	> 25 mg/mL (h γ-globulin)
▪ Bacterial Count	≤ 100 CFU/mL
▪ Endotoxin Concentration	≤ 10.0 endotoxin units/mL

▪ Pack sizes and type	25 mL, 250 mL, 1 L, 5 L, 50 L Packed in virgin Polyethylene container with Polypropylene cap.
▪ Resin Volume per Container	The indicated volume is the settled resin volume.
▪ Shipping Solvent	72 % (v/v) slurry in 20 % (v/v) ethanol
▪ Long Term Storage Conditions	20 % (v/v) ethanol
▪ Cleaning in Place / Sanitization	0.5 M NaOH or 0.1 M HCl
▪ Foreign Substance	not observed, no visual evidence
▪ Eluable Matter	< 0.1 %
▪ Shelf Life Stability	Minimum 5 years

For detailed test procedures please refer to Regulatory Support File BB-MF-3907.