



Zettachring 6, 70567 Stuttgart, Germany
 Tel: +49-711-13257-0 Fax: +49-711-13257-89
 E-Mail: info.tbq@tosoh.com
 Web: www.tosohbioscience.com

3604 Horizon Drive, Suite 100, King of Prussia, PA 19406, USA
 Tel: +1-484-805-1219 Fax: +1-610-272-3028
 E-Mail: info.tbl@tosoh.com
 Web: www.tosohbioscience.com

PRODUCT SPECIFICATION SHEET

Product Name: Toyopearl® SP-650 (strong cation exchange resin)

HW - 65

— -O-CH₂-CH₂-CH₂-SO₃

Part Numbers:

- 19822 Toyopearl SP-650S, 65 µm, 25 mL
- 08437 Toyopearl SP-650S, 65 µm, 250 mL
- 14698 Toyopearl SP-650S, 65 µm, 1 L
- 08438 Toyopearl SP-650S, 65 µm, 5 L
- 43202 Toyopearl SP-650M, 65 µm, 100 mL
- 07997 Toyopearl SP-650M, 65 µm, 250 mL
- 14699 Toyopearl SP-650M, 65 µm, 1 L
- 07998 Toyopearl SP-650M, 65 µm, 5 L
- 07994 Toyopearl SP-650C, 100 µm, 250 mL
- 14700 Toyopearl SP-650C, 100 µm, 1 L
- 07995 Toyopearl SP-650C, 100 µm, 5 L
- 21368 ToyoScreen SP-650M, 1 mL x 6 ea.
- 21369 ToyoScreen SP-650M, 5 mL x 6 ea.
- 21394 ToyoScreen IEC Cation Mix Pack,
1 mL x 3 grades x 2 ea. (CM, SP-650, SP-550)
- 21395 ToyoScreen IEC Cation Mix Pack,
5 mL x 3 grades x 2 ea. (CM, SP-650, SP-550)
- 21396 ToyoScreen IEC Mix Pack,
1 mL x 6 grades x 1 ea. (DEAE, SuperQ, QAE, CM, SP-650, SP-550)
- 21397 ToyoScreen IEC Mix Pack,
5 mL x 6 grades x 1 ea. (DEAE, SuperQ, QAE, CM, SP-650, SP-550)
- 21400 ToyoScreen Column Holder
- 42194 ToyoScreen Column Holder with fittings

Product Description: Toyopearl is a methacrylic polymer incorporating high mechanical and chemical stability. Resins are available as non-functionalised "HW" series resins for size exclusion separations, and derivatised with surface chemistries for alternative modes of chromatography such as ion exchange, hydrophobic interaction or affinity separations.

Toyopearl SP-650 chromatographic resin is designed for cation exchange chromatography. This chromatographic mode separates molecules on the basis of ionic interactions between the sample and the resin. The separation is usually accomplished in buffered aqueous solution with a gradient of increasing ionic strength. Alternatively, pH adjustment may be used for control of elution.

Formulation:

Particulate resin (spherical), available in particle sizes (mean diameter):
 35 µm = "S" grade
 65 µm = "M" grade
 100 µm = "C" grade
 Supplied as slurry in 20 % ethanol (v/v).

Physicochemical Specifications:

Appearance	White resin slurry which settles upon standing
Particle Size Distribution (>80 % within range)	20 – 50 µm for SP-650S 40 – 90 µm for SP-650M 50 – 150 µm for SP-650C

▪ Exclusion Limit	5 x10 ⁶ Dalton (globular protein)
▪ Mean Pore Diameter	1000 Å
▪ Pressure drop across the column	max. 7 bar (recommended)
▪ Operating Linear Flowrate	normally 10 – 600 cm/hour (depending on particle size)
▪ Ion Exchange Capacity	0.15 ± 0.02 meq/mL (S, M grade) 0.15 ± 0.03 meq/mL (C grade)
▪ Protein Adsorption Capacity	50 ± 10 mg/mL (Lysozyme)
▪ Bacterial Count	≤ 100 CFU/mL
▪ Endotoxin Concentration	≤ 10.0 endotoxin units/mL
▪ Pack sizes and type	50 mL, 100 mL, 250 mL, 1 L, 5 L, 50 L Packed in virgin Polyethylene container with Polypropylene cap.
▪ Resin Volume per Container	The indicated volume is the settled resin volume.
▪ Shipping Solvent	72 % (v/v) slurry in 20 % (v/v) ethanol
▪ Long Term Storage Conditions	20 % (v/v) ethanol
▪ Cleaning in Place / Sanitization	0.5 M NaOH or 0.1 M HCl
▪ Foreign Substance	not observed, no visual evidence
▪ Eluable Matter	< 0.2 %
▪ Shelf Life Stability	Minimum 5 years

For detailed test procedures please refer to Regulatory Support File BB-MF-3907.