Im Leuschnerpark 4, 64347 Griesheim, Germany Tel: +49 6155-7043700 Fax: +49 6155-80357900

E-Mail: info.tbg@tosoh.com Web: www.tosohbioscience.de 3604 Horizon Drive, Suite 100, King of Prussia, PA 19406, USA

Tel: +1 800-366-4875 Fax: +1 610-272-3028

E-Mail: info.tbl@tosoh.com Web: www.tosohbioscience.com

OPERATING CONDITIONS and SPECIFICATIONS

TSKgel® Tresyl-5PW Products

Part Numbers: 0014455 6.0 mm ID x 4.0 cm L 10 µm 0014456 7.5 mm ID x 7.5 cm L 10 µm

0016208 Tresyl-5PW 2 g dry gel SS Guard Gel Holder 0016106 10.0 mm ID x 2.0 cm L

This sheet contains the recommended operating conditions and the specifications for TSKgel Tresyl-5PW columns. Installation instructions and column care information are described in a separate Instruction Manual.

A. OPERATING CONDITIONS

Shipping Solvent: Acetone

NOTE: Wash the column with DI water before equilibrating with the coupling buffer.

Max.Flow Rate: 1.0 mL/min 6.0 mm ID x 4.0 cm L

mL/min 7.5 mm ID x 7.5 cm L 1.2

NOTE: Normal flow rates are 50 - 75% of the max. recommended flow rates. a)

> When using a viscous buffer, reduce the flow rate so as not to exceed the maximum allowable b)

pressure drop over the column.

Coupling Flow Rate: 0.2 - 0.5 ml /min 6.0 mm ID x 4.0 cm L 0.5 - 1.0

mL/min 7.5 mm ID x 7.5 cm L

Max. Pressure: MPa All columns 4.

pH Range: pH above 12 can only be used for a short time 5. 2 - 12

6. Salt Conc.: ≤ 3 M

<u><</u> 20% 7 Organic Conc.:

Temperature: ≥ 0°C 8.

0.5 - 1.0 M 9 Coupling Buffer K-phosphate (pH 8.0) or other non-amine containing buffers.

Blocking Buffer 0.1 M Tris-HCI (pH 8.0) or other amine containing buffers. 10.

The stability of the ligand determines the type and strength of the cleaning solvent. The 5PW 11. Cleaning Solvents:

matrix can be cleaned by 5 - 10 injections of up to 1/5th of the column volume with 0.1 - 0.2M NaOH, 20 - 40% acetic acid, ag. buffer in 20% organic, or urea or nonionic surfactant in buffer.

Store the column in a neutral pH buffer containing 0.02% NaN3 at a temperature between 4°C Storage:

and 10°C when it will not be used the next day. For overnight storage flush the column with the

mobile phase at 0.2 ml/min. Prevent air from entering the column!

B. SPECIFICATIONS Unlike other TSKgel columns, the chromatographic performance of Tresyl-5PW columns is not tested. Following

their manufacturing it is ensured, however, that the pressure drop over the column at the maximum recommended

flow rate (see above) is less than the maximum allowable pressure.

Batch Test Each lot of Tresyl-5PW packing has passed the specification that 1 gram of dry gel binds at

least 60 mg soybean trypsin inhibitor (STI) under the following conditions.

Immobilization Suspend 0.5 gram of freeze-dried Tresyl-5PW in 4 ml of a solution containing

0.1 M NaHCO3, 0.5 M NaCl and 40 mg soybean trypsin inhibitor (Sigma, Type 1-S). Incubate

the suspension for 1 day at 25° C while shaking.

Analysis Determine the peak height of an injection of the STI supernatant by size exclusion

chromatography. Column: TSKgel 3000SWxL 7.8 mm ID x 30.0 cm L,

Mobile Phase: 0.1 M phosphate + 0.2 M NaCl (pH 6.8), Flow Rate: 0.8 ml/min,

Sample: 5µl supernatant, Detection: UV @ 220nm.

Note our technical hotline tel +49 6155 70437-36 and e-mail, techsupport.tbg@tosoh.com

Page 1 of 1 DS 1050/ May 15 / AX