RESIN INFORMATION SHEET

Product Name TOYOPEARL® AF-Chelate-650M

(Metal chelating resin for affinity chromatography)

Part Numbers 0014475 TOYOPEARL AF-Chelate-650M, 25 mL

 0019800
 TOYOPEARL AF-Chelate-650M, 100 mL

 0014907
 TOYOPEARL AF-Chelate-650M, 1 L

 0014908
 TOYOPEARL AF-Chelate-650M, 5 L

Product Description

TOYOPEARL chromatographic resins are based on a rigid methacrylic polymer, resulting in high mechanical and chemical stability. Resins are available as non-functionalized "HW" series resins for size exclusion separations, and derivatized with surface chemistries for alternative modes of chromatography such as ion exchange, hydrophobic interaction or affinity separations.

TOYOPEARL AF-Chelate-650M is a metal chelating support for affinity chromatography. The product is prepared by introducing iminodiacetic acid onto TOYOPEARL HW-65. TOYOPEARL AF-Chelate-650M, after priming with metal ions, is used to isolate proteins containing histidine, cysteine and tryptophan residues. This resin is particularly useful for the purification of plasma proteins and other enzymes.

Operating Conditions

Packing pressure	Typically 0.3 MPa
Shipping solvent	20 % (v/v) ethanol
Shipping formulation	72 % (v/v) slurry in shipping solvent (*)
Pressure limiting factor	Depend on column hardware (typically 0.7 MPa)
Operating linear flowrate	Typically 10 - 600 cm/hour
Long-term storage conditions	20 % (v/v) ethanol
Cleaning-in-place/Sanitization	0.1 - 0.5 mol/L NaOH or 0.1 mol/L HCl

Specifications

Particle size distribution (min. 80 % within range)	40 - 90 μm
lon exchange capacity	25 - 45 meq/L
Bacterial count	Max. 100 CFU/mL
Endotoxin concentration	Max. 10.0 EU/mL
Foreign substance (colored particle)	Unobserved

Additional Information

Appearance		White resin slurry which settles upon standing
Mean pore diameter	(base resin)	100 nm (*)

^(*) The value is for reference only, not guaranteed.

Lot-specific data are included in the Certificate of Analysis (COA) shipped with the product. For detailed test procedures please refer to the appropriate Regulatory Support File.