RESIN INFORMATION SHEET

1 TO TOTALLE MILE 17 JOI	Product Name	TOYOPEARL® NH2-750F
--------------------------	--------------	---------------------

0023442

(Salt-tolerant strong cation exchange chromatography resin)

Part Numbers 0023438 TOYOPEARL NH2-750F, 100 mL

 0023439
 TOYOPEARL NH2-750F, 250 mL

 0023440
 TOYOPEARL NH2-750F, 1 L

 0023441
 TOYOPEARL NH2-750F, 5 L

TOYOPEARL NH2-750F, 50 L

Product Description

TOYOPEARL chromatographic resins are based on a rigid methacrylic polymer, resulting in high mechanical and chemical stability. Resins are available as non-functionalized "HW" series resins for size exclusion separations, and derivatized with surface chemistries for alternative modes of chromatography such as ion exchange, hydrophobic interaction or affinity separations.

TOYOPEARL NH2-750F chromatographic resins are designed for anion exchange chromatography and are alkaline durable to 0.5 mol/L NaOH. This chromatographic mode separates molecules on the basis of ionic interactions between the sample and the resin. The separation is usually accomplished in buffered aqueous solution with a gradient of increasing ionic strength. Alternatively, pH adjustment may be used for control of elution.

Operating Conditions

Packing pressure	Typically 0.3 MPa
Shipping solvent	20 % (v/v) ethanol
Shipping formulation	72 % (v/v) slurry in shipping solvent (*)
Pressure limiting factor	Depend on column hardware (typically 0.7 MPa)
Operating linear flowrate	Typically 10 - 600 cm/hour
Long-term storage conditions	20 % (v/v) ethanol (counter ion should be replaced with Cl ⁻ .)
Cleaning-in-place/Sanitization	0.1 - 0.5 mol/L NaOH or 0.1 - 0.5 mol/L HCl

Specifications

30 - 60 μm
0.07 - 0.13 eq/L
Min. 70 g/L
Max. 100 CFU/mL
Max. 10.0 EU/mL
Max. 0.2 % (for dry gel)
Max. 6

Additional Information

Appearance	White resin slurry which settles upon standing
Mean pore diameter (base resin)	> 100 nm (*)

^(*) The value is for reference only, not guaranteed.

Lot-specific data are included in the Certificate of Analysis (COA) shipped with the product. For detailed test procedures please refer to the appropriate Regulatory Support File.