



Im Leuschnerpark 4, 64347 Griesheim, Germany  
Tel: +49 6155-7043700 Fax: +49 6155-8357900  
E-Mail: info.tb@tosoh.com  
Web: www.tosohbioscience.de

3604 Horizon Drive, Suite 100, King of Prussia, PA 19406, USA  
Tel: +1 800-366-4875 Fax: +1 610-272-3028  
E-Mail: info.tbl@tosoh.com  
Web: www.tosohbioscience.com

## OPERATING CONDITIONS and SPECIFICATIONS

### TSKgel® SWXL Guardcolumn Products

<b>Part Numbers:</b>	0008543	6.0 mm ID x 4.0 cm L	Guardcolumn SWXL	7 µm
	0018008	6.0 mm ID x 4.0 cm L	Guardcolumn SWXL PEEK	7 µm

This sheet contains the recommended operating conditions and the specifications for **TSKgel** SWXL guardcolumns. Installation instructions and column care information are described in a separate Instruction Manual.

#### A. OPERATING CONDITIONS

- Shipping Solvent: 0.05% NaN<sub>3</sub> and 0.1 M Na<sub>2</sub>SO<sub>4</sub> in 0.1 M phosphate buffer, pH 6.7
- Max.Flow Rate: 1.2 mL/min

**NOTE:** When a buffer with high viscosity is used, the maximum flow rate may have to be reduced so as not to exceed the maximum pressure drop. When changing solvents, use a flow rate equal to 25% of the maximum flow rate.

- Standard Flow Rate: 0.5 - 1.0 mL/min
- Max. Pressure: 7.0 MPa
- pH Range: 2.5 - 7.5
- Salt Conc.: ≤ 0.5 Molar
- Organic Conc.: 0 - 100% for aqueous soluble organic solvents. Make gradual solvent changes using a shallow
- Temperature: 10 - 30°C Reduce flow rate when operating below 10°C.
- Cleaning Solvents:
  - (1) conc. salt solution at low pH, e.g. 0.5 M Na<sub>2</sub>SO<sub>4</sub>, pH 2.7
  - (2) methanol or acetonitrile in low conc. aqueous buffer, or, if nothing else is successful,
  - (3) buffered solution of SDS, urea or guanidine

**NOTE:** Choose a cleaning solvent based on sample properties, e.g. use (1) to remove basic proteins, and (2) to remove hydrophobic proteins. Chaotropic agents can solvate strongly adsorbed proteins, e.g. via hydrogen bonding.

- Storage: Store the column in mobile phase containing 0.05% NaN<sub>3</sub> when it will not be used the next day. For overnight storage flush the column with mobile phase at low flow rate. Prevent air from entering the column!
- Column Protection: The use of guard columns is recommended to prolong the life of the analytical column. Guard column life depends greatly on sample cleanliness. As a general rule, guard columns should be replaced after every 30-40 sample injections, when the peaks become excessively wide, or when the peaks show splitting.
- Top-Off: Occasionally, due to accident, sample, mobile phase or operational variables, a depression can develop at the guard column inlet. Use **TSKgel** Top-Off SWXL (P/N 08544) for filling in such voids.